

Used at along all No Outlet/Dead End streets



Used at along all Private streets



Note:

- Street Name shall be minimum 6" letter height
- Block Number shall be minimum 3" letter height
- Street Suffix shall be minimum 3" letter height
- All street name blades that are location at an intersection with an arterial street shall have the logo added to the left side of the name blade on the arterial street with Private tab for the private street
- Minimum 3" space between street name and block number
- A 1" border shall be located around street name blade
- Town of Flower Mound Logo shall be 4" in height, 7" in width and spaced 2.5" from the top and bottom of sign name blade, and 1" between logo and street name.
- Street Name Blade shall be 9" in height and up to 60" in width
- Sign Name Blades blank shall be 0.080" thick
- Retroreflective sheeting for all arterial signs shall be Diamond Grade Cubed or equal, all others shall be a minimum of High Intensity Prismatic or equal.
- All sign specs not shown on this detail shall conform to the latest edition of the Town of Flower Mound Sign Specifications.
- All sign shall conform to the latest edition of the Texas Manual on Uniform Traffic Control Devices.
- All sign shall use Clearview Hwy1 or Hwy2 font with using a capital letter for the first letter of each word with the remainder being lowercase.
- Screening process is prohibited. Sheeting MUST be applied using the reverse weed process.
- Private tab shall be a minimum 9" X 10" with "Private" lettering 3" in height at a 45 degree angle.
- Private tab shall be located on the end of the street name blade that faces the private street
- Dead End/No Outlet Street shall have a No Outlet tab a minimum 9" X 10" with yellow background and black legend
- No Outlet tab shall be located on the end of the street name blade that faces the no outlet street

	STANDARD PAVING DETAIL	DATE: OCT 2009
	SIGN NAME BLADE DETAIL	SHEET 2 OF 3
		SHEET: ST-11